Permatex, Inc. 10 Columbus Blvd. Hartford, CT 06106 USA **Telephone: 1-87-Permatex** 

(877) 376-2839

Emergency: 800-255-3924

Balderson RECD OCT 31 2007

# **Material Safety Data Sheet**

#### 1. PRODUCT IDENTIFICATION

**Product Name:** 

27BR SENSOR SAFE HI TEMP SILICONE RTV 3 OZ

item No:

81422

**Product Type:** 

Silicone

2. CON	POSITION/INFO	RMATION ON INGREI	DIENTS
Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	>60	Not Listed	Not Listed
AMORPHOUS SILICA 7631-86-9	5-15	10 mg/m³ TWA	6 mg/m³ TWA
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	5-15	5 mg/m³ TWA (oil mist)	5 mg/m³ PEL (oil mist)
ETHYLTRIACETOXYSILANE 17689-77-9	1-10	Not Listed	Not Listed
METHYLTRIACETOXYSILANE 4253-34-3	1-10	Not Listed	Not Listed
POLYDIMETHYLSILOXANE 63148-62-9	1-10	Not Listed	Not Listed
ACETIC ACID 64-19-7	***	10 ppm TWA; 25 mg/m³ TWA	10 ppm TWA; 25 mg/m³ TWA

# 3. HAZARDS IDENTIFICATION

**Toxicity:** 

May cause eye and skin irritation. May irritate lips, gums, tongue, mouth, nose and throat. May irritate respiratory system upon frequent or prolonged use. \*\*\*\*When this product is exposed to moisture. acetic acid may be formed. Note: This product does not contain microcyrstalline silica.

**Primary Routes of Entry:** 

Eye and skin contact, ingestion, inhalation.

Signs and Symptoms of Exposure: Acetic acid produced during curing irritates eyes, nose and throat.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
AMORPHOUS SILICA	5-15			Group 3 Monograph 68,
7631-86-9			2	1997

Being Aggravated by Exposure:

Medical Conditions Recognized as Methyltriacetoxysilane: Eye, skin and pulmonary disorders.

# 4. FIRST AID MEASURES

Ingestion: Inhalation:

Rinse mouth. If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Move to fresh air in case of accidental inhalation of vapors. Obtain medical attention.

**Skin Contact:** 

Wipe off paste with paper towel or cloth. Wash with soap and water. Seek medical attention if irritation persists..

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical

**Eye Contact:** attention if irritation persists.

### 5. FIRE FIGHTING MEASURES

Flash Point (°F/C):

Recommended Extinguishing Media: **Special Fire-Fighting Procedures:** 

**Hazardous Products of Combustion:** 

Unusual Fire/Explosion Hazards:

More than 200 degrees F. Method: Tag Closed Cup

Carbon Dioxide, Dry Chemicals, Foam.

Water spray may be ineffective on flames but should be used to keep

fire-exposed containers cool.

Oxides of carbon, Metal oxide fumes, Oxides of silicon, Chlorine,

Formaldehyde, Acetic acid

Product name: 27BR SENSOR SAFE HI TEMP

SILICONE RTV 3 OZ

**Lower Explosive Limit: Upper Explosive Limit:** 

Not determined

Not determined

6. ACCIDENTAL RELEASE MEASURES

**Spill Procedures:** 

Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

Item No: 81422

7. HANDLING AND STORAGE

Storage:

Store away from water or moisture Keep away from oxidizers.

Handling:

Avoid contact with skin and eyes. Do not wear contact lenses. Use only in a well ventilated area. Do

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses.

Skin:

Neoprene, rubber or butyl rubber gloves.

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure

limits (or to the lowest feasible levels when limits have not been established) during the use of this

**Respiratory Protection:** 

Not required under normal use. An approved respirator (i.e. NIOSH, etc.) should be worn when

exposures are expected to exceed the applicable limits.

Comments:

When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the

OSHA permissible limit for formaldehyde.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Red paste

Odor:

Acetic acid

**Boiling Point:** 

Not applicable, polymeric material Does not apply

pH:

Polymerized

Solubility in Water: Specific Gravity:

1.05 @ 60 degrees F.

VOC Content(Wt.%):

Not determined

Vapor Pressure:

Less than 5 mm hg @ 70 degrees F.

Vapor Density (Air=1):

Not Determined Not Determined

**Evaporation Rate:** 

10. STABILITY AND REACTIVITY

**Chemical Stability:** 

Stable at normal conditions

**Hazardous Polymerization:** 

WILL NOT OCCUR

Incompatabilities:

Polymerized by contact with moisture. Acetic acid liberated.

Conditions to Avoid:

Exposure to moisture

**Hazardous Products of Combustion:** 

Oxides of carbon. Metal oxide fumes. Oxides of silicon. Chlorine.

Formaldehyde. Acetic acid.

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

**US EPA Waste Number:** 

NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

**DOT (49CFR 172)** 

**Domestic Ground Transport** 

DOT Shipping Name:

Unrestricted

**Hazard Class:** 

None

2 of 3

# <u>Product name:</u> 27BR SENSOR SAFE HI TEMP SILICONE RTV 3 OZ

UN/ID Number:

None

Marine Pollutant:

None

IATA

**Proper Shipping Name:** 

Not regulated

Class or Division: UN/NA Number:

None None

**IMDG** 

**Proper Shipping:** 

Unrestricted

Hazard Class: UN Number:

None None

### **15. REGULATORY INFORMATION**

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

**SARA 313 Information** 

NONE

**CALIFORNIA PROP 65:** 

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

**TSCA Inventory Status:** 

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

**Estimated NFPA Rating:** 

HEALTH 2, FLAMMABILITY 1, REACTIVITY 1

**Estimated HMIS Classification:** 

HEALTH 2, FLAMMABILILTY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By:

Denise Boyd, Health and Safety Manager

Company:

Permatex. Inc. 10 Columbus Blvd. Hartford, CT USA

06106

Revision Date: 09/08/2005

Item No: 81422

Revision

Number: