

REC'D MAY 10 2002

Dondzila
KCT



MATERIAL SAFETY DATA SHEET

SECTION 1 - MANUFACTURER OR SUPPLIER DATA

MSDS NUMBER

100989

MANUFACTURER'S NAME & MAILING ADDRESS U S Chemical Corporation 316 Hart Street Watertown, Wisconsin 53094 USA		PREPARED BY D. E. Kinas	SIGNATURE David E. Kinas
EMERGENCY TELEPHONE NO. (24 HOUR SERVICE) Medical Emergency ONLY: 1-800-851-7145 Ext. 075		TITLE Quality Assurance Manager	DATE 12-20-99
		PRODUCT INFORMATION TELEPHONE NO. (8 AM TO 5 PM CST, MON-FRI) Product Information: 1-800-558-9566	

SECTION 2 - IDENTITY OF MATERIAL

PRODUCT NAME ULTRA ACTIVE SUDS			
PRODUCT DESCRIPTION High Surfactant Laundry Suds		FORMULA Proprietary Blend	CHEMICAL FAMILY N.A.
REGULATED IDENTIFICATION	DOT PROPER SHIPPING NAME N.A. (Combustible Exception)		
	SHIPPING ID NUMBER N.A.	PACKING GROUP N.A.	HAZARD CLASS N.A.

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT N.A.	SPECIFIC GRAVITY (H ₂ O = 1) 1.000	PHYSICAL FORM Liquid	COLOR Bright Blue
VAPOR PRESSURE (mm Hg) N.A.	MELTING POINT N.A.	SOLUBILITY IN WATER Complete	SCENT None Added
VAPOR DENSITY (AIR = 1) N.A.	EVAPORATION RATE (BUTYL ACETATE = 1) N.A.	pH 2500 ppm SOLUTION N.A.	pH CONCENTRATE 6.0
OTHER Slightly Viscous Solution with alcohol odor.			

SECTION 4 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS (CHEMICAL NAME; COMMON NAME)	OSHA PEL	ACSH TLV	OTHER LIMITS RECOMMENDED	PERCENT WT/WT
Isopropanol: Isopropyl Alcohol CAS Registry Number 67-63-1	400 ppm TWA	400 ppm TWA	500 ppm STEL (ACGIH/OSHA)	1.0-5.0
2-Butoxyethanol: Butyl Cellosolve CAS Registry Number 111-76-2	25 ppm TWA-Skin	25 ppm TWA-Skin	None	7.0-13.0

This product contains no other ingredient considered hazardous according to the criteria of 29 CFR 1910.1200, OSHA. However, this product contains chemicals which may be subject to reporting requirements according to the criteria of SARA Title III, 40 CFR, Part 370, Section 311 and Section 312. This product also contains chemicals which may be subject to reporting requirements according to the criteria of SARA Title III, 40 CFR, Part 372, Section 313.

STATE RIGHT TO KNOW INFORMATION

THIS PRODUCT CONTAINS: WATER/7732-18-5, NONOXYNOL/9016-45-9, BUTYL CELLOSOLVE/111-76-2, ISOPROPYL ALCOHOL/67-63-0, POLYACRYLIC ACID/9003-01-4

NFPA RATING: Health-1/Flammability-2/Reactivity-0 See Section 5 for Protective Equipment.
 EHIS RATING: Health-1/Flammability-2/Reactivity-0 See Section 5 for Protective Equipment.

CARCINOGENICITY:

This product does not contain any known carcinogens or anticipated carcinogens according to the criteria of the NTP Annual Report on Carcinogens, IARC Monographs, and OSHA 29 CFR 1910, Subpart Z.

(CONTINUED IN SECTIONS 5 TO 8)

SECTION 5 - SAFE USAGE DATA

PROTECTIVE EQUIPMENT TYPES	EYES	Safety glasses with side shields and an eye-wash station.
	RESPIRATORY	None required with normal use.
	OTHER	None required with normal use.
	OTHER	If major exposure is possible to eyes/skin, wear/use appropriate protective equipment.
VENTILATION	GENERAL MECHANICAL	Satisfactory. Maintain adequate ventilation. Keep levels below recommended TLV.
	LOCAL EXHAUST	Not ordinarily needed. Avoid inhalation of mists containing this product.
PRECAUTIONS	HANDLING & STORAGE	Follow all label directions. Instruct personnel about proper use, hazards, precautions, and first-aid measures. Avoid inhalation, ingestion and contact with skin and eyes.
	OTHER	Rotate stock regularly. Handle carefully to avoid damaging container. Keep container closed when not in use. Recommended storage temp below 100°F. Do not freeze. Keep out of children's reach.

SECTION 6 - HEALTH HAZARD DATA

EFFECTS OF EXPOSURE	INHALATION	Excessive amounts may cause coughing, irritation to nose, throat and mucous membranes, nausea, dizziness, and headache. Diluted solutions have reduced effects.
	INGESTION	May cause tissue damage to the digestive tract, nausea, vomiting, dizziness, headache, red blood cell hemolysis and possible liver and kidney damage.
	SKIN & EYES	SKIN: Contact may cause irritation, drying, defatting and dermatitis. EYES: Contact may cause irritation, and possible corneal damage. Prolonged direct contact may cause eye damage.
	ACUTE & CHRONIC	ACUTE: Irritation to skin, eyes, and respiratory system. CHRONIC: Ingestion or repeated over-exposure may cause liver and kidney damage.
TARGET ORGANS		
ROUTES OF ENTRY		
INGESTION-X SKIN ABSORPTION-X TARGET ORGANS		
SKIN-X EYES-X INHALATION-X Skin, Eyes, Respiratory System, Blood, Liver, Kidneys.		

SECTION 7 - PHYSICAL HAZARD DATA

FLAMMABILITY	LFL = Approx. 1.0%	FLASH POINT = 145°F	METHOD USED = Tag Closed Cup
	UEL = Approx. 10.6%	See Section 8: Fire-Unusual Hazards	
STABILITY	STABLE	X	CONDITIONS TO AVOID Avoid mixing with any other cleaning product. Mix only with water. Do not store at high temperatures. Recommended storage temp. <100°F.
	UNSTABLE		HAZARDOUS DECOMPOSITION PRODUCTS Burning can produce carbon monoxide, carbon dioxide, and other fumes.
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	N.A.
INCOMPATIBILITY	MATERIALS TO AVOID		
	Strong Alkalies, Bleach or Sodium Hypochlorite and Other Oxidizing Agents.		

SECTION 8 - EMERGENCY RESPONSE DATA

FIRE	EXTINGUISHING MEDIA	To fight fire, use carbon dioxide, dry chemical or alcohol foam.
	SPECIAL PROCEDURES	Evacuate area of unprotected personnel. Wear protective clothing including a NIOSH-approved self-contained breathing apparatus.
	UNUSUAL HAZARDS	This product has not been tested as a whole for LFL and UEL values. However, the values are listed for 2-Butoxyethanol, the component contributing to this hazard.
FIRST AID MEASURES	INGESTION	Do not induce vomiting. If patient is conscious and can swallow, administer milk or water.
	SKIN	Remove contaminated clothes, flood with water for 15 minutes. EYES: Flood with lukewarm (not hot) water poured from a large glass 2 or 3 inches from eyes. Remove contacts. Have patient blink as much as possible while flooding the eyes. Continue for 15 minutes. INHALATION: Move victim to fresh air. Give artificial respiration if patient is not breathing. ADMINISTER FIRST AID TREATMENT AS STATED ABOVE, THEN CALL 1-800-851-7145 Ext 075 OR CONTACT PHYSICIAN FOR FURTHER MEDICAL INSTRUCTIONS.
SPILLS	STEPS TO BE TAKEN	Wear proper protective equipment including rubber boots. Stop leak if you can do so without risk. Dike or dam large spills. Ventilate area if needed. Soak up with sand or other non-combustible inert absorbent materials. Flush area with water and follow with normal clean-up procedures. Keep combustibles away. Be careful as spills are slippery.
	WASTE DISPOSAL METHOD	Comply with all federal, state, and local regulations. Consult state and local authorities for restrictions on disposal of chemical waste. If approved, may be diluted and drained to a municipal sewer or waste treatment plant. Rinse empty container thoroughly with water before discarding. Please recycle empty container whenever possible.

THE DATA IN THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND DOES NOT RELATE TO ITS USE IN COMBINATION WITH ANY OTHER MATERIAL OR PROCESS. THE DATA CONTAINED IS BELIEVED TO BE ACCURATE, HOWEVER, SINCE USE CONDITIONS VARY AND ARE OUTSIDE OUR CONTROL, THE MANUFACTURER MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, AND ASSUMES NO LIABILITY FOR FAILURE TO FOLLOW PRODUCT USE DIRECTIONS AND SAFETY PRECAUTIONS.