Permatex, Inc. 10 Columbus Blvd. Hartford, CT 06106 USA Telephone: 1-87-Permatex

(877) 376-2839

Emergency: 800-255-3924

International Emergency: 813-248-0585

Balderson //cotc REC'D APR 18 2007

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name:

BEARING MOUNT FOR RELAXED FITS 36ML

Item No:

68040

Product Type:

Anaerobic

2. COMPOSITION/INFORMATION ON INGREDIENTS					
Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:		
AROMATIC DIMETHACRYLATE ESTER 24448-20-2	40-50	Not Listed	Not Listed		
DIMETHACRYLATE ESTER 27813-02-1	30-40	Not Listed	Not Listed		
BISPHENOL A FUMARATE RESIN 39382-25-7	10-20	Not Listed	Not Listed		
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<3	Not Listed	Not Listed		
SACCHARIN 31-07-2	0.5-4.0	10mg/m³ nuisance dust	Not Listed		

3. HAZARDS IDENTIFICATION

Toxicity:

Primary Routes of Entry:

May be harmful if swallowed. Causes eye irritation. May cause moderate skin irritation.

Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure:

Repeated skin contact may cause allergic skin reactions. Contact with eyes may cause tearing and

redness. Ingestion may cause nausea and vomiting.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
SACCHARIN 81-07-2	0.5-4.0	Delisted April 2000		Group 3: Vol 73, Page 517: 1999

Medical Conditions Recognized as

Being Aggravated by Exposure:

Preexisting skin disorders.

4. FIRST AID MEASURES

Ingestion:

Inhalation:

If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention. Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed.

Skin Contact:

Obtain medical attention.

Eye Contact:

Wash off with soap and water. If skin irritation persists, call a physician.

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical

attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C):

Recommended Extinguishing Media: **Special Fire-Fighting Procedures:** Hazardous Products of Combustion: Unusual Fire/Explosion Hazards:

More than 200 degrees F. Method: Tag Closed Cup Water fog, carbon dioxide, foam, dry chemical.

Firefighters should wear self-contained breathing apparatus.

Irritating vapors

None.

Lower Explosive Limit: **Upper Explosive Limit:**

Not determined Not determined

ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until

disposal.

7. HANDLING AND STORAGE

Storage:

Store below 100 degrees F.

Handling:

Avoid prolonged skin contact. Keep away from eyes. Do not inhale vapors.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses

Skin:

Rubber or plastic gloves.

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure

limits (or to the lowest feasible levels when limits have not been established) during the use of this

Respiratory Protection:

An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the

applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Green liquid

Odor: **Boiling Point:** **IRRITATING** More than 300 degrees F.

pH:

Does not apply

Solubility in Water:

Slight

Specific Gravity:

1.09 @ 25 degrees C.

VOC Content(Wt.%):

Not determined

Vapor Pressure:

Less than 10 mm Hg @ 80 degrees F.

Vapor Density (Air=1):

Heavier than air

Evaporation Rate:

Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability:

Hazardous Polymerization:

Incompatabilities:

Conditions to Avoid:

Hazardous Products of Combustion:

Stable at normal conditions

WILL NOT OCCUR.

Reducing agents

Heat

Irritating vapors

TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number:

NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name:

Unrestricted

Hazard Class: UN/ID Number:

None None

Marine Pollutant:

None

IATA

Proper Shipping Name:

Not regulated

Class or Division:

None

UN/NA Number:

None

IMDG

Proper Shipping:

Unrestricted

Hazard Class:

None

UN Number:

None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

DIMETHYLBENZYL HYDROPEROXIDE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating:

HEALTH 2, FLAMMABILITY 1, REACTIVITY 1

Estimated HMIS Classification:

HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By:

Denise Boyd, Health and Safety Manager

Revision Date: 02/25/2005

Company:

Permatex. Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision 2

Number: