

MATERIAL SAFETY DATA SHEET


Manufactured by:

SURFLEX[®]
SERIES

Anderson

Chemical Company

325 SOUTH DAVIS AVENUE
LITCHFIELD, MINNESOTA 55355
(320) 693-2477



Product Name: Reclaim

24-HOUR EMERGENCY PHONE #: 1-800-424-9300 (CHEMTREC)

Revised: 11/24/2008 Imt

Supersedes: 1/8/2007

I. IDENTIFICATION

Chemical Name And Synonyms:

Not applicable

DOT Shipping Name

Corrosive Solid, basic, inorganic, n.o.s.
(Sodium hydroxide, Sodium Metasilicate, Anhydrous)

Chemical Family:

Alkali

DOT Hazard Class & I.D. Number

Corrosive Material UN3262

PG

8 II

II. HAZARDOUS INGREDIENTS

Component	CAS NO.	%	TLV	PEL	Toxic	Hazard
Sodium hydroxide	1310-73-2	30	2 mg/M3	2 mg/M3	NA	Corrosive to skin and eyes.
Sodium dichloroisocyanurate	51580-86-0	3	3mg/M3	3mg/M3	NA	Corrosive to skin and eyes.
Sodium Metasilicate, Anhydrous	6834-92-0	15	Not est.	Not Est.	NA	Irritant to eyes and mucous membranes.
Sodium Carbonate	497-19-8	<15	NE	NE		Irritant to eyes, skin, and mucous membranes.

**Toxic chemical subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR §372). NA: Not applicable
NE: Not established

III. PHYSICAL DATA

Boiling Point: Not applicable

Specific Gravity: Not applicable

Appearance: White solid

Form: Solid

pH, 1% Soln.: 12.5

Solubility In Water: Complete

Odor: Not applicable

IV. FIRE AND EXPLOSION HAZARD DATA

Flashpoint: Not Applicable

Extinguishing Media: Not applicable.

Special Fire

Fighting Procedures: Although this product is not combustible, if a fire occurs in the near vicinity, good firefighting practice dictates the use of self-contained breathing apparatus and other protective gear. Cool fire-exposed containers with water. Move fire exposed containers if it can be done without risk.

Unusual Fire And

Explosion Hazards: If the container breaks, the product should be handled with care as it is corrosive.

V. HEALTH HAZARD DATA

Carcinogenic: The raw materials used in this product are not considered to be a carcinogen by ACGIH and OSHA.

Effects Of Over-exposure: Corrosive. Causes irritation (possibly severe), burns to the eyes. May cause permanent eye damage. Causes irritation (possibly severe), burns to the skin. Causes irritation (possibly severe) to the respiratory tract. Causes irritation (possibly severe), burns, nausea, vomiting to the gastrointestinal tract. The severity of effects depend on concentration and how soon after exposure the area is washed.

Emergency And First

Aid Procedures: **Eyes:** Flush immediately with water for 15 minutes. Lift upper and lower eyelids for complete rinsing. Get immediate medical attention.
Skin: Flush with water for 15 minutes. If irritation persists after rinsing, get medical attention. Remove contaminated clothing and wash before reuse. Discard contaminated leather goods.

Ingestion: Rinse mouth with water. Give water to dilute. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to a semi-comatose, comatose, convulsing or unconscious person.

Inhalation: Move person to fresh air. If breathing stops, administer artificial respiration. If breathing is difficult, have a trained person administer oxygen. Get immediate medical attention.

* NFPA/HMIS Degree or Hazard: 4 = Extreme; 3 = High; 2 = Moderate; 1 = Slight; 0 = Insignificant.

Continued On Back

HMIS A. Safety Glasses B. Safety Glasses, Gloves C. Safety Glasses, Gloves, Apron D. Face Shield, Gloves, Apron E. Safety Glasses, Gloves, Dust Respirator F. Safety Glasses, Gloves, Apron, Dust Respirator G. Safety Glasses, Gloves, Vapor Respirator H. Splash Goggles, Gloves, Apron, Vapor Respirator I. Safety Glasses, Gloves, Vapor and Dust Respirator J. Splash Goggles, Gloves, Apron, Vapor and Dust Respirator K. Air Line, Hood or Mask, Gloves, Full Suit, Boots X. Ask your supervisor for guidance.

VI. REACTIVITY DATA

Stability - Unstable:

Stable: X

Conditions To Avoid: Mixing with water, acid or incompatible materials may cause splattering and release of large amounts of heat. Will react with some metals forming flammable hydrogen gas.

Incompatibility: Acids, halogenated compounds, prolonged contact with aluminum, brass, bronze, copper, lead, tin, zinc or other alkali sensitive metals or alloys. Avoid contact with leather, wool, organic nitro compounds. Reacts with strong acids and will yield chlorine gas.
(Materials To Avoid)

Hazardous

Decomposition Products: At flame temperatures, chlorine gas may be liberated. Toxic fumes of sodium oxide.

VII. SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released Or Spilled:

Small spills can be diluted with a large amount of water and flushed to sanitary sewer. For large spills, wear appropriate personal protection equipment. Completely contain spilled material with dikes or sandbags, etc., and prevent run-off into ground or surface waters or sewers. Recover as much material as possible into containers for disposal or reuse. Remaining material may be diluted with water; neutralize chlorine by adding sodium sulfite, sodium bisulfite or sodium thiosulfate; then neutralize alkalinity by adding a dilute acid. Flush spill area with water followed by a liberal covering of sodium bicarbonate. Neutralization products, both solid and liquid, must be recovered for disposal.

Waste Disposal Method: Dispose of in accordance with local, state, and federal regulations.

VIII. SPECIAL PROTECTION INFORMATION

Respiratory Protection: Respiratory protection is not required for normal use. If mist level is high, wear NIOSH approved respirator.

Ventilation: Should be adequate to keep mist level below the TLV.

Protective Gloves: Natural rubber, neoprene or nitrile gloves should be worn.

Eye Protection: Safety glasses with side shields. Chemical goggles, face shield if appropriate.

Protective Clothing: In situations where contact with can be anticipated, protective clothing should be worn.

IX. SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling And Storing:

Do not get in eyes, on skin, or clothing. Wash thoroughly after handling. Wear appropriate protective clothing/equipment. Do not breathe vapors or mists. Use with adequate ventilation. Keep containers tightly closed and properly labeled. Safety shower and eyewash stations should be provided in the areas where this product is handled. Containers that have been emptied will retain product residue and should be handled as if they were full.

Other Precautions: Not applicable.

X. REVISED INFORMATION

MSDS Status: Supplier update