

Permatex, Inc.  
10 Columbus Blvd.  
Hartford, CT 06106 USA  
Telephone: 1-87-Permatex  
(877) 376-2839  
Emergency: 800-255-3924  
International Emergency: 813-248-0585

*Balderson*  
*KAC*

REC'D OCT 31 2007

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

Product Name: 26BR HIGH TEMP RTV RED SILICONE GASKET MAKER 3 OZ  
Item No: 81160  
Product Type: Silicone

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	>60	Not Listed	Not Listed
AMORPHOUS SILICA 7631-86-9	5-15	10 mg/m <sup>3</sup> TWA	6 mg/m <sup>3</sup> TWA
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE 64742-46-7	1-10	5 mg/m <sup>3</sup> TWA (oil mist)	5 mg/m <sup>3</sup> PEL (oil mist)
IRON OXIDE 1309-37-1	1-10	5 mg/m <sup>3</sup> TWA (dust and fume, as Fe)	10 mg/m <sup>3</sup> TWA
ETHYLTRIACETOXSILANE 17689-77-9	1-10	Not Listed	Not Listed
METHYLTRIACETOXSILANE 4253-34-3	1-10	Not Listed	Not Listed
POLYDIMETHYLSILOXANE 63148-62-9	1-10	Not Listed	Not Listed
TITANIUM DIOXIDE 13463-67-7	1-10	10 mg/m <sup>3</sup> TWA ACGIH	15 mg/m <sup>3</sup> TWA (total dust)
ACETIC ACID 64-19-7	****	10 ppm TWA; 25 mg/m <sup>3</sup> TWA	10 ppm TWA; 25 mg/m <sup>3</sup> TWA

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye and skin irritation. May irritate lips, gums, tongue, mouth, nose and throat. \*\*\*\*When this product is exposed to moisture, acetic acid may be formed. May irritate respiratory system upon frequent or prolonged use. Note: This product does not contain microcrystalline silica.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation

**Signs and Symptoms of Exposure:** Acetic acid produced during curing irritates eyes, nose and throat..

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
AMORPHOUS SILICA 7631-86-9	5-15			Group 3 Monograph 68, 1997
IRON OXIDE 1309-37-1	1-10		A4 - Not Classifiable	Group 3, Supplement 7 1987; Monograph 1 1972
TITANIUM DIOXIDE 13463-67-7	1-10	male rat-negative, female rat-negative, male mice-negative, female mice-negative	A4	Group 2B; Vol 93,2006; Vol 47,1989

**Medical Conditions Recognized as Being Aggravated by Exposure:** Methyltriacetoxysilane: Eye, skin and pulmonary disorders.

### 4. FIRST AID MEASURES

**Ingestion:** Rinse mouth. If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

**Skin Contact:** Wipe off paste with paper towel or cloth. Wash off with soap and water. If skin irritation persists, call a physician.

**Product Name:** 26BR HIGH TEMP RTV RED SILICONE  
GASKET MAKER 3 OZ

**Item No:** 81160

#### **4. FIRST AID MEASURES**

**Eye Contact:**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

#### **5. FIRE FIGHTING MEASURES**

**Flash Point (°F/C):**

**Recommended Extinguishing Media:**

**Special Fire-Fighting Procedures:**

**Hazardous Products of Combustion:**

**Unusual Fire/Explosion Hazards:**

More than 200 degrees F. Method: Tag Closed Cup

Carbon Dioxide, Dry Chemicals, Foam.

Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Acetic acid, Formaldehyde, Silica fume, Oxides of nitrogen, Oxides of carbon, Oxides of sulfur, Metal oxide fumes

None.

**Lower Explosive Limit:**

Acetic acid: 4%

**Upper Explosive Limit:**

Acetic acid: 19.9% @ 200 degrees F.

#### **6. ACCIDENTAL RELEASE MEASURES**

**Spill Procedures:**

Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

#### **7. HANDLING AND STORAGE**

**Storage:**

Store away from water or moisture. Keep away from oxidizers.

**Handling:**

Avoid contact with skin and eyes. Do not wear contact lenses. Use only in a well ventilated area. Do not take internally.

#### **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Eyes:**

Safety glasses

**Skin:**

Neoprene or nitrile gloves recommended.

**Ventilation:**

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

**Respiratory Protection:**

Not required under normal use. An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

**Comments:**

When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde.

#### **9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:**

Red paste

**Odor:**

Acetic acid

**Boiling Point:**

Not applicable, polymeric material

**pH:**

Does not apply

**Solubility in Water:**

Polymerized

**Specific Gravity:**

1.0

**VOC Content(Wt.%):**

3.0% by weight; 0.25 lb/gal; 30 g/l

**Vapor Pressure:**

10 mm Hg @ 80 degrees F.

**Vapor Density (Air=1):**

Not Determined

**Evaporation Rate:**

Not Determined

#### **10. STABILITY AND REACTIVITY**

**Chemical Stability:**

Stable at normal conditions

**Hazardous Polymerization:**

Will not occur.

**Incompatibilities:**

Polymerized by contact with moisture. Acetic acid liberated.

**Conditions to Avoid:**

Exposure to moisture

**Hazardous Products of Combustion:**

Acetic acid, Formaldehyde, Silica fume, Oxides of nitrogen, Oxides of carbon, Oxides of sulfur, Metal oxide fumes

#### **11. TOXICOLOGICAL INFORMATION**

See Section 3

**Product Name:** 26BR HIGH TEMP RTV RED SILICONE  
GASKET MAKER 3 OZ

**Item No:** 81160

## **12. ECOLOGICAL INFORMATION**

No data available

## **13. DISPOSAL CONSIDERATIONS**

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.  
**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material

## **14. TRANSPORTATION INFORMATION**

**DOT (49CFR 172)**

### **Domestic Ground Transport**

<b>DOT Shipping Name:</b>	Unrestricted
<b>Hazard Class:</b>	None
<b>UN/ID Number:</b>	None
<b>Marine Pollutant:</b>	None

### **IATA**

<b>Proper Shipping Name:</b>	Not regulated
<b>Class or Division:</b>	None
<b>UN/NA Number:</b>	None

### **IMDG**

<b>Proper Shipping:</b>	Unrestricted
<b>Hazard Class:</b>	None
<b>UN Number:</b>	None

## **15. REGULATORY INFORMATION**

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

### **CALIFORNIA PROP 65:**

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

### **TSCA Inventory Status:**

**Listed on Inventory:** YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

## **16. OTHER INFORMATION**

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 1, REACTIVITY 0

**Estimated HMIS Classification:** HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Prepared By:** Denise Boyd, Health and Safety Manager  
**Company:** Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

**Revision Date:** 12/14/2006

**Revision** 6

**Number:**

**Telephone No.:** 1-87-Permatex (877) 376-2839