

Keystone  **Steel & Wire**

REC'D AUG 26 2003

Wong/Kate

MATERIAL SAFETY DATA SHEET

IDENTITY: **LOW CARBON STEEL PRODUCTS - ALL GRADES**

SECTION I

Manufacturer's Name:
KEYSTONE STEEL & WIRE CO.Emergency Telephone No.:
309-697-7020Address:
7000 SW ADAMS ST.
PEORIA, IL 61641Telephone No. for Information:
309-697-7020

Date Prepared: September 18, 1998

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components:	OSHA PEL (mg/M3)	ACGIH TLV (mg/M3)	%
Iron CAS No. 7439-89-6	10 (as Fe ₂ O ₃ fume)	5 (as Fe ₂ O ₃ fume)	>99
Manganese CAS No. 7439-96-5	5	1.0 (as fume)	<1
Zinc CAS No. 1314-13-2	5-Fume or Respirable dust 10 Total dust	5-Fume 10-Dust	*
Lime	5	5	*

Percentages are representative of product and may vary depending on batch composition. Due to the variance in batch composition, trace quantities of antimony, arsenic, barium, beryllium, cadmium, chromium, copper, lead, mercury, nickel, selenium, silver, and thallium may be present in amounts <1%.

* A thin coating of oil, lime (<0.5% of total weight of product), or zinc (<2.4 % total weight of product) may be added to the surface as a corrosion inhibitor or preventative.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	N/A	Specific Gravity:	Approx. 8
Vapor Pressure (mm Hg):	N/A	Melting Point:	2800°F
Vapor Density (Air = 1):	N/A	Evap. Rate (Butyl Acetate = 1):	N/A
Solubility in Water:	Negligible		
Appearance and Odor:	odorless solid with metallic luster		

Low Carbon Steel Products
Material Safety Data Sheet
Page 2 of 4

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): N/A Flammable Limits: N/A
Extinguishing Media: Dry Compound or Dry Powder
Special Fire Fighting Procedures: NIOSH approved positive pressure, self contained breathing apparatus.
Unusual Fire and Explosion Hazards: Spraying water on molten metal may cause an explosion. Use a dry type extinguisher. Product is non-combustible.

SECTION V - REACTIVITY DATA

Stability: Unstable _____
 Stable XX Conditions to Avoid: N/A

Incompatibility (Materials to Avoid): Strong acids or bases

Hazardous Decomposition or By-Products: Metal fumes and certain noxious gases such as CO may be produced during welding or burning operations.

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY:	Inhalation?	Skin?	Ingestion?
	XX	XX	

Health Hazards (Acute and Chronic): No toxic effects are expected from its inert form. Prolonged, repeated exposure to fumes or dusts generated during heating, cutting, welding, or brazing may cause the following health effects:

Inhalation:

- Iron (Fe): Siderosis, no fibrosis
- Manganese (Mn): Pneumonitis. CNS involvement, including irritability, difficulty in walking, speech disorders, compulsive behavior, masklike face, and Parkinson like syndrome.
- Zinc (Zn): Zinc oxide fumes can cause metal fume fever with symptoms similar to flu: chills, fever, headache, cough, nausea, diarrhea, vomiting, etc.
- Soluble Oil: Pulmonary effects
- Lime: May cause irritation.

Skin Contact:

- May cause irritation. Soluble oil may cause dermatitis.

Eye Contact:

- May cause irritation.

Ingestion:

- May cause irritation to mouth and throat.

Low Carbon Steel Products
Material Safety Data Sheet
Page 3 of 4

CARCINOGENICITY: NTP? IARC Monographs? OSHA Regulated?
No No No

Sign and Symptoms of Exposure: Zinc: Metal Fume Fever
Manganese: irritability, difficulty in walking, speech disorders, compulsive behavior, masklike face, and Parkinson like syndrome.

Medical Conditions Generally Aggravated by Exposure: None found

Emergency First Aid Procedures: Inhalation - If inhaled in large amounts, remove exposed person to fresh air. Get medical attention.
Ingestion - Call a physician. If swallowed, if conscious, induce vomiting immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING USE

Steps To Be Taken in Case Material Is Released or Spilled:
Sweep up spill and place in a container.

Waste Disposal Method: Dispose in accordance with all applicable federal, state, and local environmental regulations. Can often be sold for scrap metal.

Precautions To Be Taken In Handling and Storage: N/A

Other Precautions: Avoid breathing fume or dust. Store away from strong acids and bases.

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specific Type): NIOSH approved dust and fume cartridge respirator or supplied air if airborne dust or fume levels are or may be above the PEL.

Consult respirator manufacturer for assistance in choosing appropriate respirator. If respirators are used, employees must have a respirator program which complies with OSHA 1910.134

Ventilation: Local Exhaust - Use to maintain airborne levels below PEL.

Protective Gloves: Standard

Eye Protection: As necessary to protect against particles or radiation from welding type operations.

Other Protective Clothing or Equipment: As needed to protect against heat.

Work/Hygienic Practices: Use good personal hygiene to avoid ingestion or inhalation through food or smoking.

Low Carbon Steel Products
Material Safety Data Sheet
Page 4 of 4

SARA 313 INFORMATION:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>CHEMICAL NAME</u>	<u>CAS NUMBER</u>	<u>CONCENTRATION</u>
Zinc	1314-13-2	<2.4%
Manganese	7439-96-5	<1%

Percentages are representative of product and may vary depending on batch composition.

The information herein is provided in good faith and is believed to be correct and complete as of the date issued. This document is intended as a guide to appropriate handling precautions for the material. The user is responsible for determining the precautions and dangers of this material for his or her particular application.

No representations or warranties either expressed or implied of merchantability, fitness for a particular purpose or any other nature are made with respect to either the information set forth herein or to the product to which the information refers.

Keystone Steel and Wire shall not be liable for any loss or damage directly or indirectly arising from the use of this product. Keystone Steel and Wire assumes no obligation or liability for reliance on the information contained in this data sheet.