

DEEP FLEX PLASTIC MOLDS, INC.
1200 PARK AV. PO BOX 1257
MURFREESBORO, TN 37133-1257

Prepared: March 7, 1994
Emergency phone: (216) 467-4195

Information phone: (615) 896-1111

SECTION I - PRODUCT INFORMATION

Product Name: Deep Flex Super Gloss
Formula: TM-3105
Synonyms: Super Gloss
Chemical Family: Pressurized product

Fox/KCT REC'D JUN 02 2004

SECTION II - HAZARDOUS INGREDIENTS

Material or Component	CAS#	%	TLV	Carc.
*2-Butoxyethanol	111-76-2	4.0	25ppm	
*N-Butanol	71-36-3	<3.0	100ppm	
Isobutyl Acetate	110-19-0	13.9	150ppm	
*Methyl Ethyl Ketone	78-93-3	16.0	200ppm	
*Acetone	67-64-1	17.0	1000ppm	
*Toluene	108-88-3	6.0	200ppm	
*Xylene	1330-20-7	5.0	100ppm	
Propane/Isobutane	74-98-6	25.0	1000ppm	
Non Hazardous	-	11.0	-	

SECTION III - PHYSICAL DATA

Boiling Point: NA
Specific Gravity: NA
Vapor Density (air=1): >1
Evaporation Rate (ether=1): NA
Appearance and Odor: Clear spray - solvent odor

Melting Point: NA
Vapor Pressure: <130 psi at 140 F
% Volatile: 87.7%
Solubility in H2O: <1%

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point-Test Method: Below 20 F TOC
Flammable Limits: Lower- NA Upper- NA
Extinguishing Media: Waterfog, Foam CO2, or dry chemical
Special Fire Fighting Procedures: Keep containers cool. Use equipment or shielding required to protect personnel against bursting or venting containers.
Unusual Fire & Explosion Hazards: At elevated temperatures (130 F or over) containers may vent, rupture, or burst.

SECTION V - HEALTH HAZARD DATA

Permissible Exposure Level: NA
Threshold Limit Value: NA for multi-component products.
EFFECTS OF OVEREXPOSURE:

Eyes: Irritant
Skin: Mild irritant
Inhalation: Harmful if inhaled.
Ingestion: NA

ACUTE OVEREXPOSURE- May cause dizziness or, in extreme case, absence of oxygen could produce narcosis.

All chemical compounds marked with an asterisk (*) are toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372. You must notify each person to whom this mixture or trade name product is sold. This statement must remain a part of this Material Safety Data Sheet. This statement must not be detached. Any copy or redistribution of this Material Safety Data Sheet shall include this statement.

CHRONIC OVEREXPOSURE- Tests have shown that exposure to methylene chloride over an extended period of time (years) has produced cancer in laboratory animals. Chronic overexposure (occupational, for example) may cause permanent brain and/or central nervous system disorders.

AGENCY FIRST AID PROCEDURES-

Eyes: Flush eyes with plenty of water. Continue for 15 minutes. Get medical attention.

Skin: Wash with soap and water.

Inhalation: Remove to fresh air.

Ingestion: Get medical attention.

SECTION VI - REACTIVITY DATA

Stability - Material is stable under non-emergency conditions.

Hazardous Polymerization will not occur.

Hazardous Decomposition Products: Oxides of carbon and water.

Conditions To Avoid: Heat, open flame, sparks. Containers could rupture above 130 F.

Materials To Avoid: None.

SECTION VII - SPILL AND LEAK PROCEDURES

If spilled or leaked: Flush with large quantities of water. Ventilate area.

Small Quantities: Same

Large Quantities: Same

Waste Disposal: Dispose of in accordance with local, State and Federal regulations.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

Respiratory Protection: Use appropriate respirator (NIOSH/MSHA approved)

Ventilation: Normal use - normal ventilation.

Skin Protection: Synthetic or rubber gloves recommended as good hygiene practice.

Eye Protection: Safety or chemical goggles may be desirable when using this product.

Other Protective Equipment: None

SECTION IX - SPECIAL PRECAUTIONS

Storage: Read and follow cautions on product label. Do not store in temperatures above 120 F.

Other Precautions: Avoid using this product or other aerosols in confined spaces with little or no ventilation.

Disclaimer: While Deep Flex Plastic Molds, Inc. believes that the data contained herein are accurate and derived from qualified sources the data are not to be taken as a warranty or representation for which Deep Flex assumes legal responsibility. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations.

NA - Not Applicable

NE - Not Established

An acceptable ceiling concentration for toluene is 300 ppm. Acceptable maximum peak above the acceptable ceiling concentration for an 8 hour shift is 500 ppm or 10 minutes for toluene.