ACE HARDWARE CORP

-- 183A129, SEVEN STAR FLAT LATEX WALL

MSDS Safety Information

FSC: 8010

MSDS Date: 08/09/1991

MSDS Num: BXYLJ LIIN: 00N061255

Product ID: 183A129, SEVEN STAR FLAT LATEX WALL PAINT

MFN: 01

Responsible Party

Cage: ACEHA

Name: ACE HARDWARE CORP

Address: 21901 SOUTH CENTRAL AVE

City: MATTESON IL 60443

Info Phone Number: 708-720-0600

Emergency Phone Number: 708-990-0600

Published: Y

Contractor Summary

Cage: ACEHA

Name: ACE HARDWARE CORPORATION

Address: 21901 SOUTH CENTRAL AVENUE

City: MATTESON IL 60443

Phone: 708-720-0600

Ingredients

Cas: 13463-67-7 RTECS #: XR2275000

Name: TITANIUM OXIDE; (TITANIUM DIOXIDE)

% Wt: 17.9

OSHA PEL: 15 MG/M3 TDUST ACGIH TLV: 10 MG/M3 TDUST

Cas: 1317-65-3

RTECS #: EV9580000

Name: CALCIUM CARBONATE

% Wt: 22.5

OSHA PEL: 15 MG/M3 TDUST ACGIH TLV: 10 MG/M3 TDUST

Cas: 66402-68-4

Name: KAOLIN; (ALUMINUM SILICATE).

% Wt: 13.3

OSHA PEL: 5 MG/M3 (MFR) ACGIH TLV: 5 MG/M3 (MFR)

Cas: 37244-96-5

Name: NEPHELINE SYENITE

% Wt: 3.1

OSHA PEL: N/K (FP N)
ACGIH TLV: 5 MG/M3 (MFR)

Cas: 124-68-5

RTECS #: UA5950000

Name: 1-PROPANOL, 2-AMINO-2-METHYL-; (2-AMINO-2-METHYL-1-PROPANOL)

임 Wt: 0.2

OSHA PEL: 20 PPM (MFR) ACGIH TLV: 10 PPM (MFR)

Cas: 7664-41-7

RTECS #: BO0875000

Name: AMMONIA (SARA 302/313) (CERCLA)

용 Wt: <0.1

OSHA PEL: 50 PPM

ACGIH TLV: 25 PPM; 35 STEL

EPA Rpt Qty: 100 LBS DOT Rpt Qty: 100 LBS

Health Hazards Data

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route Of Entry Inds - Inhalation: YES

Skin: YES

Inqestion: NO

Carcinogenicity Inds - NTP: NO

IARC: NO OSHA: NO

Effects of Exposure: ACUTE: IN CONFINED AREA VAPORS IN HIGH CONC ARE ANESTHETIC, IRRIT TO UPPER RESP SYSTEM. MAY CAUSE LIGHTHEADEDNESS & STAGGERED GAIT.

Explanation Of Carcinogenicity: NOT RELEVANT.

Signs And Symptions Of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated By Exposure: CHRONIC PROBLEMS WITH RESPIRATORY MAY BE AGGRAVATED BY EXPOSURE TO VAPORS.

First Aid: INHAL: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH FROM SKIN W/SOAP & WATER. LAUNDER CONTAMD CLTHG BE REUSE. EYES: FLUSH W/WATER FOR AT LEAST 15 MINS. GET MED AID. INGES MD IMMEDIATELY(FP N).

Handling and Disposal

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE & REMOVE W/INERT ABSORBENT.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: INCINERATE IN APPROVED FACILITY. DO NOT INCINE CLOSED CONTAINERS. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE & LO REGULATIONS REGARDING POLLUTION.

C 10 E 10 0 0 0

Handling And Storage Precautions: DOL STORAGE CATEGORY 3B.

Other Precautions: KEEP OUT OF REACH OF CHILDREN.

Fire and Explosion Hazard Information

Flash Point Text: 199F,93C

Extinguishing Media: NON-COMBUSTIBLE. FOR DRY SOLIDS, USE WATER, FOAM CHEMICALS.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECT EQUIPMENT(FP N). WATER MAY BE USED TO COOL CLOSED CONTAINERS.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS EXPOSED TO EXTREME HE RUPTURE DUE TO PRESSURE BUILD-UP. CONTENTS MAY SPATTER IF TEMPERATUR 212F.

Control Measures

Respiratory Protection: DEVICE APPROVED BY NIOSH/MSHA.

Ventilation: LOCAL EXHAUST: PREFERABLE. MECH(GENL): ACCEPTABLE.

Protective Gloves: IMPERVIOUS GLOVES(FP N).

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGS (FP N).

Other Protective Equipment: EMERGENCY EYEWASH & DELUGE SHOWER MEETING DESIGN CRITERIA(FP N).

Work Hygienic Practices: AVOID BREATHING VAPOR OR SPRAY MIST. AVOID CO WITH SKIN & EYES.

Supplemental Safety and Health: NONE SPECIFIED BY MANUFACTURER.

Physical/Chemical Properties

B.P. Text: 212F,100C Vapor Density: HVR/AIR Spec Gravity: 1.35(H*20=1)

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: INSOLUBLE

Appearance and Odor: COLORED PIGMENTED LIQUID W/SLIGHT ODOR.

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.

Materials To Avoid: NO HAZARDOUS REACTIONS ARE EXPECTED UNDER NORMAL U

Hazardous Decomposition Products: CARBON DIOXIDE & CARBON MONOXIDE.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT.

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

HAZCOM Label

Product ID: 183A129, SEVEN STAR FLAT LATEX WALL PAINT

Cage: ACEHA

Company Name: ACE HARDWARE CORPORATION

Street: 21901 SOUTH CENTRAL AVENUE

City: MATTESON IL Zipcode: 60443

Health Emergency Phone: 708-720-6600

Label Required IND: Y

Date Of Label Review: 07/12/1995

Status Code: C

Label Date: 07/12/1995 Origination Code: G Eye Protection IND: YES Skin Protection IND: YES

Signal Word: WARNING

Respiratory Protection IND: YES

Health Hazard: Moderate Contact Hazard: None Fire Hazard: Slight Reactivity Hazard: None

Hazard And Precautions: ACUTE: IN CONFINED AREA, VAPORS IN HIGH CONCEN ARE ANESTHETIC, IRRITATION TO UPPER RESPIRATORY SYSTEM. MAY CAUSE LIGHTHEADEDNESS & STAGGERED GAIT. CHRONIC: NONE SPECIFIED BY

MANUFACTURER.

Disclaimer (provided with this information by the compiling agencies): information is formulated for use by elements of the Department of D The United States of America in no manner whatsoever expressly or im warrants, states, or intends said information to have any applicatio viability by or to any person or persons outside the Department of D nor any person or persons contracting with any instrumentality of th States of America and disclaims all liability for such use. Any pers utilizing this instruction who is not a military or civilian employe United States of America should seek competent professional advice t and assume responsibility for the suitability of this information to particular situation regardless of similarity to a corresponding Dep of Defense or other government situation.