

IN CASE OF EMERGENCY CALL CHEMTREC AT
1-800-424-9300

Wong HCTC

REC'D JUL 13 2006

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)
PM Battery

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name KUNG LONG BATTERIES INDUSTRIAL CO., LTD.	Emergency Telephone Number 886-2-5810413
Address (Number, Street, City, State, and ZIP Code) P.O. BOX 10397	Telephone Number for Information 886-2-5810413
TAIPEI, TAIWAN R.O.C.	Date Prepared FEB. 18, 1993
	Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Lead	CAS #7439-92-1 0.050 mg/m ³	0.15 mg/m ³		50%
Lead Oxides	CAS #7439-92-1 0.050 mg/m ³	0.15 mg/m ³		25%
Sulfuric Acid, 1.28 s.g.	CAS #7664-93-9 1.0 mg/m ³	2.0 mg/m ³		18%

THIS PRODUCT IS AN ARTICLE UNDER OSHA.

Section III — Physical/Chemical Characteristics

Bolling Point	N/A	Specific Gravity (H ₂ O = 1)	N/A
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	N/A		
Appearance and Odor	N/A		

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) Direct Flame to Battery Case	Flammable Limits UL-94HB	LEL N/A	UEL N/A
Extinguishing Media Water, Foam, Dry			
Special Fire Fighting Procedures N/A			

Unusual Fire and Explosion Hazards
ep lighted cigarettes, sparks and flames away. Explosion can result from improper charging

and ignition of charging gases. Explosion can result if charged in gas tight enclosures.

Produce locally