

Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924
International Emergency: 813-248-0585

Balderson
KAC

REC'D OCT 31 2007

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: POWER BEAD ULTRA BLUE SILCONE RTV 9.5OZ AE
Item No: 85519
Product Type: Silicone (Barrier Pack)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	30-40	Not Listed	Not Listed
CALCIUM CARBONATE 471-34-1	20-30	10 mg/m ³ particulate TWA	Not Listed
LIMESTONE 1317-65-3	10-20	Not Listed	15 mg/m ³ TWA (total dust); 5 mg/m ³ TWA (respirable)
POLYBUTYLENE RESIN 9003-29-6	10-20	Not Listed	Not Listed
VINYL OXIMINOSILANE 2224-33-1	1-10	Not Listed	Not Listed
STEARIC ACID 57-11-4	1-10	Not Listed	Not Listed
NITROGEN 7727-37-9	****	Asphyxiant	Not Listed
2-BUTANONE OXIME 96-29-7	****	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. May irritate lips, gums, tongue, mouth, nose and throat. May be harmful if swallowed. When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde. ****When this product is exposed to moisture, butanone oxime may be formed.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: ****Butanone oxime produced during curing is toxic and irritates eyes, nose and throat. Overexposure to the silane may cause coma and respiratory failure..

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting skin disorders.

4. FIRST AID MEASURES

Ingestion: Rinse mouth. If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapors. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact: Wipe off paste with paper towel or cloth. Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C):

Recommended Extinguishing Media:

Special Fire-Fighting Procedures:

More than 200 degrees F. (base material) Method: Tag Closed Cup
Carbon Dioxide, Dry Chemicals, Foam.

***Warning: This container is pressurized with nitrogen. Do not remove rubber plug. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Product name: POWER BEAD ULTRA BLUE SILCONE
RTV 9.5OZ AE

Item No: 85519

5. FIRE FIGHTING MEASURES

Hazardous Products of Combustion:

Silica fume, Formaldehyde, Oxides of nitrogen, Oxides of carbon, Methyl ethyl ketone, possibly methyl ethyl ketoxime
Contents under pressure. Heated cans may burst. Use equipment or shielding to protect personnel from bursting containers.

Unusual Fire/Explosion Hazards:

Lower Explosive Limit:

Not determined

Upper Explosive Limit:

Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F. Exposure to high temperatures may cause container to burst.

Handling:

Avoid contact with skin and eyes. Do not inhale vapors.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses

Skin:

Rubber or plastic gloves.

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection:

Not required under normal use. In case of insufficient ventilation, wear suitable respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Blue paste

Odor:

MILD

Boiling Point:

Not applicable, polymeric material

pH:

Does not apply

Solubility in Water:

Polymerized

Specific Gravity:

1.3

VOC Content(Wt.%):

3.8% by weight

Vapor Pressure:

<5 mm Hg @ 70°F

Vapor Density (Air=1):

3.0

Evaporation Rate:

Slower than butyl acetate

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

WILL NOT OCCUR.

Incompatibilities:

Strong oxidizers, Polymerized by contact with moisture.

Conditions to Avoid:

Exposure to moisture. Heat.

Hazardous Products of Combustion:

Silica fume, Formaldehyde, Oxides of nitrogen, Oxides of carbon, Methyl ethyl ketone, possibly methyl ethyl ketoxime

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number: D003 - (Can under pressure) Hazardous waste per 40CFR 261.23(6)

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name:

CONSUMER COMMODITY

Product name: POWER BEAD ULTRA BLUE SILCONE
RTV 9.5OZ AE

Item No: 85519

Hazard Class: ORM-D
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)
Class or Division: Class 9
UN/NA Number: ID 8000

IMDG

Proper Shipping: Aerosols, Limited Quantity
Hazard Class: Class 2.2
UN Number: UN 1950

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: 09/13/2006
Revision Number: 3