

Safety Data Sheet



Revision Date 06-Oct-2014
Version 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product name P.O.G (Paint, Oil & Grease)
Product code W.20090
Recommended Use Professional Carpet Cleaning

Manufacturer Chemspec
901 North Newkirk Street
Baltimore, MD 21205

Emergency telephone number Chemtrec: 1-800-424-9300 for US
+1 703-527-3887 outside US

2. Hazards identification

Emergency Overview

May cause central nervous system depression
May cause adverse kidney effects

Potential Health Effects

Acute toxicity

Eyes

May cause slight irritation.

Skin

No known effect based on information supplied.

Inhalation

May be harmful if inhaled.

Ingestion

No known effect based on information supplied.

Chronic Effects

May cause adverse liver effects. Ethylene glycol monobutyl ether (CAS#111-76-2): Laboratory studies on experimental animals indicate that exposure may cause red blood cell damage and damage to the kidney and liver. These effects have not been observed in humans. Laboratory animal studies have reported adverse reproductive and developmental effects from overexposure.

Aggravated Medical Conditions

Central nervous system. Preexisting eye disorders. Blood disorders. Kidney disorders. Liver disorders. Skin disorders. Respiratory disorders. Hematopoietic system.

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

Environmental hazard

See Section 12 for additional Ecological Information.

3. Composition/information on ingredients

Component	CAS-No	Weight %
AMYL ACETATE 628-63-7 (10-30)	628-63-7	10-30
2-METHYLBUTYL ACETATE 624-41-9 (10-30)	624-41-9	10-30
ETHANOL, 2-BUTOXY- 111-76-2 (1-10)	111-76-2	1-10

4. First aid measures

General advice	Show this material safety data sheet to the doctor in attendance.
Eye contact	Remove contact lenses. Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin contact	Wash off immediately with soap and plenty of water. Remove all contaminated clothes and shoes.
Inhalation	Move to fresh air.
Ingestion	Gently wipe or rinse the inside of the mouth with water.
Notes to physician	Treat symptomatically.

5. Fire-fighting measures

Flammable Properties	Not flammable.
Flash point	106 °F / 41 °C
Suitable extinguishing media	Water spray. Foam. Dry powder.
Explosion Data	
Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.
Protective Equipment and Precautions for Firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions	Use personal protective equipment.
Environmental precautions	No special environmental precautions required.
Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

7. Handling and storage

Advice on safe handling	Wear personal protective equipment.
Technical measures/Storage conditions	Use only in area provided with appropriate exhaust ventilation. Keep tightly closed in a dry and cool place.

8. Exposure controls/personal protection

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico
AMYL ACETATE 628-63-7	STEL: 100 ppm TWA: 50 ppm	TWA: 100 ppm TWA: 525 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 1000 ppm TWA: 100 ppm TWA: 525 mg/m ³	TWA: 100 ppm TWA: 530 mg/m ³ STEL: 150 ppm STEL: 800 mg/m ³
2-METHYLBUTYL ACETATE 624-41-9	STEL: 100 ppm TWA: 50 ppm			

ETHANOL, 2-BUTOXY- 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³	TWA: 26 ppm TWA: 120 mg/m ³ STEL: 75 ppm STEL: 360 mg/m ³
Component	British Columbia	Alberta	Quebec	Ontario TWAEV
AMYL ACETATE 628-63-7 (10-30)	TWA: 50 ppm STEL: 100 ppm	TWA: 50 ppm TWA: 266 mg/m ³ STEL: 100 ppm STEL: 532 mg/m ³	TWA: 50 ppm TWA: 266 mg/m ³ STEL: 100 ppm STEL: 532 mg/m ³	TWA: 50 ppm STEL: 100 ppm
2-METHYLBUTYL ACETATE 624-41-9 (10-30)	TWA: 50 ppm STEL: 100 ppm		TWA: 50 ppm TWA: 266 mg/m ³ STEL: 100 ppm STEL: 532 mg/m ³	TWA: 50 ppm STEL: 100 ppm
ETHANOL, 2-BUTOXY- 111-76-2 (1-10)	TWA: 20 ppm	TWA: 20 ppm TWA: 97 mg/m ³	TWA: 20 ppm TWA: 97 mg/m ³	TWA: 20 ppm

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Engineering Measures

Showers
Eyewash stations
Ventilation systems.

Personal Protective Equipment**Hand Protection**

Rubber/latex/neoprene or other suitable chemical resistant gloves

Eye/Face Protection

Safety glasses with side-shields. Tightly fitting safety goggles.

Skin and body protection

Skin and body protection.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

When using, do not eat, drink or smoke.

9. Physical and chemical properties

Physical state

Liquid

Appearance

Clear liquid

Odor

Banana

Color

colorless

Property**Values****Remarks • Methods****pH**

no data available

Boiling point/boiling range**Flash Point**

41 °C / 106 °F

Evaporation rate

no data available

Explosion Limits**upper****lower****Vapor pressure**

no data available

Vapor density

no data available

Specific Gravity

0.875

Viscosity, kinematic

no data available

Water solubility

no data available

Partition coefficient: n-octanol/water

no data available

Explosive properties

no data available

Other information

Volatile organic compounds (VOC) 70%
content

Melting/freezing point

10. Stability and reactivity

Stability/Reactivity Stable under recommended storage conditions.

Incompatible products None known based on information supplied.

Conditions to Avoid Direct sources of heat.

Hazardous Decomposition Products Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

Hazardous Polymerization Hazardous polymerization does not occur.

11. Toxicological information

Acute toxicity

Product Information The product itself has not been tested.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
ETHANOL, 2-BUTOXY-	470 mg/kg (Rat)	99 mg/kg (Rabbit)	450 ppm (Rat) 4 h

Chronic toxicity

Chronic toxicity May cause adverse liver effects
Ethylene glycol monobutyl ether (CAS#111-76-2): Laboratory studies on experimental animals indicate that exposure may cause red blood cell damage and damage to the kidney and liver. These effects have not been observed in humans. Laboratory animal studies have reported adverse reproductive and developmental effects from overexposure

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA	Mexico
ETHANOL, 2-BUTOXY-	A3	Group 3			

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Target Organ Effects Blood Central nervous system Eyes Hematopoietic System Kidney Liver Respiratory system Skin

12. Ecological information

Ecotoxicity

No information available. .

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms	Toxicity to other organisms
AMYL ACETATE		LC50: 96 h Lepomis macrochirus 650 mg/L static			
ETHANOL, 2-BUTOXY-		LC50: 96 h Lepomis macrochirus 1490 mg/L static LC50: 96 h Lepomis macrochirus 2950 mg/L	EC50: 48 h Daphnia magna 1000 mg/L		

Persistence and degradability No information available.

Bioaccumulation .

Mobility No information available.

Chemical Name	log Pow
ETHANOL, 2-BUTOXY-	0.81

13. Disposal considerations

Waste Disposal Methods This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

US EPA Waste Number D001

California Hazardous Waste Codes 561

14. Transport information

DOT Not regulated

MEX Not regulated

15. Regulatory information

International Inventories

TSCA	Complies
DSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies
NZIoC	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

"-" - Unknown. Not listed.

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

P.O.G (Paint, Oil & Grease)

Chemical Name	Weight %	SARA 313 - Threshold Values %
ETHANOL, 2-BUTOXY-	1-10	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
AMYL ACETATE	5000 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
AMYL ACETATE	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
AMYL ACETATE	X	X	X		
ETHANOL, 2-BUTOXY-	X	X	X	X	

International Regulations

Mexico - Grade Moderate risk, Grade 2

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B3 Combustible liquid



16. Other information

NFPA	Health Hazard 2	Flammability 2	Stability/Reactivity 0	Physical and chemical hazards -
HMIS	Health Hazard 2	Flammability 2	Physical Hazard 0	Personal protection -

Prepared By Chemspec Regulatory Affairs/Product Safety

Revision Date 06-Oct-2014

Revision Note

No information available.

Legend:

NIOSH IDLH: Immediately Dangerous to Life or Health

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Material Safety Data Sheet